


## Technical data sheet

Article number:  
111-00734

T50R



|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Product Group</b>               | Cable Ties for outdoor use (UV-resistant)                                                                              |
| <b>Product Family</b>              | T-Series in PA66W black                                                                                                |
| <b>Material</b>                    | Polyamide 6.6, UV-resistant (PA66W)                                                                                    |
| <b>Colour</b>                      | Black (BK)                                                                                                             |
| <b>Application Range</b>           | Outdoor Use                                                                                                            |
| <b>Application Tool</b>            | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Bundle Ø max.</b>               | 50.0 mm                                                                                                                |
| <b>Bundle Ø min.</b>               | 1.5 mm                                                                                                                 |
| <b>Flammability</b>                | UL 94 V2                                                                                                               |
| <b>Halogen-free</b>                | Yes                                                                                                                    |
| <b>Length (L)</b>                  | 202 mm                                                                                                                 |
| <b>Min.Tensile Strength</b>        | 225 N                                                                                                                  |
| <b>Operating Temperature</b>       | -40 °C to +85 °C                                                                                                       |
| <b>Package Content packed in</b>   | bag                                                                                                                    |
| <b>Pack Cont.</b>                  | 100 pcs.                                                                                                               |
| <b>Releasable Closure (Yes/No)</b> | No                                                                                                                     |
| <b>Specifications</b>              | ANSI/UL 1565, ANSI/UL 62275, EN 50149:1999, IEC 62275:2006                                                             |
| <b>Thickness (T)</b>               | 1.2 mm                                                                                                                 |
| <b>Toothing (Serration)</b>        | Inside Serrated                                                                                                        |
| <b>UL-File Number</b>              | E64962                                                                                                                 |
| <b>Variant</b>                     | Inside Serrated                                                                                                        |
| <b>Width (W)</b>                   | 4.6 mm                                                                                                                 |

