

## Technical data sheet

**Article number:**  
**111-00790**

**LK3A**

<b>Product Group</b>	Cable ties in-between size to T-Series
<b>Product Family</b>	LK-Series
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>Colour</b>	Natural (NA)
<b>Application Range</b>	High Temperature and Outdoor Use
<b>Application Tool</b>	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Diameter max (metric)</b>	70.0 mm
<b>Bundle Ø min.</b>	2.5 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	281 mm
<b>Min.Tensile Strength</b>	360 N
<b>Operating Temperature</b>	-40 °C to +110 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	ANSI/UL 1565, ANSI/UL 62275
<b>Thickness (T)</b>	1.6 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64962
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	8.7 mm

