

Technical data sheet

Article number:
111-00817

SHT18R



| | |
|------------------------------------|---|
| Product Group | Cable Ties for temperatures up to + 195 °C (500 h) in Polyamide 4.6 |
| Product Family | T-Series in PA46 |
| Material | Polyamide 4.6 (PA46) |
| Colour | Natural (NA) |
| Application Range | High Temperature and Outdoor Use |
| Application Tool | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7ISP |
| Bundle Ø max. | 22.0 mm |
| Bundle Ø min. | 1.0 mm |
| Flammability | UL 94 V2 |
| Halogen-free | Yes |
| Length (L) | 100.0 mm |
| Min.Tensile Strength | 80 N |
| Operating Temperature | -40 °C to +130 °C |
| Package Content packed in | bag |
| Pack Cont. | 1000 pcs. |
| Releasable Closure (Yes/No) | No |
| Specifications | ANSI/UL 1565, ANSI/UL 62275 |
| Thickness (T) | 1.2 mm |
| Toothing (Serration) | Inside Serrated |
| UL-File Number | E64962 |
| Variant | Inside Serrated |
| Width (W) | 1.8 mm |

