


## Technical data sheet

Article number:  
111-00882

**T250S(B)**



|                                    |   |
|------------------------------------|---|
| <b>Product Group</b>               | Cable Ties Polyamide 6.6 standard   |
| <b>Product Family</b>              | T-Series in PA66 black  |
| <b>Material</b>                    | Polyamide 6.6 (PA66)  |
| <b>Colour</b>                      | Black (BK)  |
| <b>Application Tool</b>            | ProCut 9 no battery, MK9P, MK9P w/ Upper air, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9ISP, EVO9iHT |
| <b>Bundle Ø max.</b>               | 50.0 mm   |
| <b>Bundle Ø min.</b>               | 12.0 mm   |
| <b>Flammability</b>                | UL 94 V2  |
| <b>Halogen-free</b>                | Yes   |
| <b>Height (H)</b>                  | 12.5 mm   |
| <b>Length (L)</b>                  | 235.0 mm  |
| <b>Min.Tensile Strength</b>        | 1115 N  |
| <b>Operating Temperature</b>       | -40 °C to +85 °C  |
| <b>Pack Cont.</b>                  | 50 pcs.   |
| <b>Releasable Closure (Yes/No)</b> | No  |
| <b>Thickness (T)</b>               | 2.0 mm  |
| <b>Toothing (Serration)</b>        | Inside Serrated   |
| <b>Variant</b>                     | Inside Serrated   |
| <b>Width (W)</b>                   | 13.1 mm   |

