

## Technical data sheet

Article number:  
111-00930

T255R



<b>Product Group</b>	Cable Ties inside serrated
<b>Material</b>	Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, MK9P, MK9P w/ Upper air, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	127.0 mm
<b>Bundle Ø min.</b>	12.5 mm
<b>Flammability</b>	UL 94 HB
<b>Length (L)</b>	508.0 mm
<b>Min.Tensile Strength</b>	1115 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	25 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	UL-ZODZ2.E64139
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64139
<b>UV-resistant acc. to ASTM D6779 (Yes/No)</b>	Yes
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	12.7 mm

