

## Technical data sheet

Article number:  
111-00950

T50I



|                             |                                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
| Product Group               | Cable Ties Polyamide 6.6 standard                                                                                      |
| Product Family              | T-Series in PA66 black                                                                                                 |
| Material                    | Polyamide 6.6 (PA66)                                                                                                   |
| Colour                      | Black (BK)                                                                                                             |
| Application Tool            | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max.               | 80.0 mm                                                                                                                |
| Bundle Ø min.               | 1.5 mm                                                                                                                 |
| Flammability                | UL 94 V2                                                                                                               |
| Halogen-free                | Yes                                                                                                                    |
| Length (L)                  | 305.0 mm                                                                                                               |
| Min.Tensile Strength        | 225 N                                                                                                                  |
| Operating Temperature       | -40 °C to +85 °C, (+105 °C, 500 h)                                                                                     |
| Pack Cont.                  | 100 pcs.                                                                                                               |
| Releasable Closure (Yes/No) | No                                                                                                                     |
| Specifications              | ANSI/UL 62275, csa-C22.2 no. 62275                                                                                     |
| Toothing (Serration)        | Inside Serrated                                                                                                        |
| UL-File Number              | E85319                                                                                                                 |
| Variant                     | Inside Serrated                                                                                                        |
| Width (W)                   | 4.6 mm                                                                                                                 |

