Technical data sheet

| Article number:<br>111-01032 | T18R  |
|------------------------------|---|
| L<br>[]]]                    |   |
|                              |   |
| Product Group                | Cable ties for temperatures up to $+$ 105°C (heat stabilised) |
| Product Family               | T-Series in PA66HS black                                      |
| Material                     | Polyamide 6.6, heat stabilised (PA66HS)                       |
| Colour                       | Black (BK)  |
|                              |   |
| Bundle Ø max.                | 22.0 mm   |
| Bundle Ø min.                | 1.5 mm  |
| Flammability                 | UL 94 V2  |
| Halogen-free                 | Yes   |
| Height (H)                   | 3.7 mm  |
| Length (L)                   | 100.0 mm  |
| Min.Tensile Strength         | 80 N  |
| Operating Temperature        | -40 °C to +105 °C   |
| Package Content packed in    | bag   |
| Pack Cont.                   | 1000 pcs.   |
| Releasable Closure (Yes/No)  | No  |
| Thickness (T)                | 1.0 mm  |
| Toothing (Serration)         | Inside Serrated   |
| Variant                      | Inside Serrated   |
| Width (W)                    | 2.5 mm  |
|                              |   |

HF RoHS

Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.