

Technical data sheet

Article number:
111-01125

T120R



Product Group	Cable Ties for higher chemical resistance for temperatures up to +170 °C in Ethylentetrafluorineethylene
Product Family	T-Series in E/TFE
Material	Ethylene Tetrafluoroethylene (E/TFE)
Colour	Blue (BU)
Application Range	High Temperature Environments
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	105.0 mm
Bundle Ø min.	15.0 mm
Flammability	UL 94 V0
Height (H)	7.35 mm
Length (L)	387.0 mm
Min.Tensile Strength	535 N
Operating Temperature	-80 °C to +170 °C
Package Content packed in	pack
Pack Cont.	50 pcs.
Releasable Closure (Yes/No)	No
Specifications	ANSI/UL 1565, ANSI/UL 62275, ANSI/UL 746B
Thickness (T)	1.9 mm
Toothing (Serration)	Inside Serrated
UL-File Number	E193818
UV-resistant acc. to ASTM D6779 (Yes/No)	Yes
Variant	Inside Serrated
Weight/Unit	0.0052 kg
Width (W)	7.4 mm

