

## Technical data sheet

**Article number:**  
**111-01579**

**AB250**

<b>Product Group</b>	Cable Ties for heat, UV-resistance and made of Polyamide 6.6 (PA66)
<b>Product Family</b>	AB-Series cable ties
<b>Material</b>	Polyamide 6.6, heat and UV-resistant (PA66HSW)
<b>Colour</b>	Grey (GY)
<b>Application Range</b>	High Temperature Environments
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
<b>Bundle Diameter max (metric)</b>	65 mm
<b>Bundle Ø min.</b>	1.5 mm
<b>Flammability</b>	UL 94 V2
<b>Length (L)</b>	251 mm
<b>Min.Tensile Strength</b>	270 N
<b>Operating Temperature</b>	-40 °C to +110 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Thickness (T)</b>	1.5 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	4.8 mm

**RoHS** 