


## Technical data sheet

Article number:  
111-01588

**MBT27HFCRFID**



<b>Product Group</b>	Stainless steel ties with RFID transponder
<b>Product Family</b>	MBTRFID – High frequency (HF), blank
<b>Material</b>	Stainless Steel (SS316), Polyester (SP)
<b>Colour</b>	Red (RD)
<b>Application Tool</b>	KST-STG200, HDT16, MK9SST, MK9PSST, RFID-HS9BT-HF, RFID-DT22-HF, RFID - IOS READER, RFID-PNR-HF-R
<b>Bundle Ø max.</b>	203 mm
<b>Bundle Ø min.</b>	17 mm
<b>Data Retention</b>	Up to 60 years
<b>Fixation Method</b>	None
<b>Flammability</b>	non-burning (except coating)
<b>Frequency</b>	13.56 MHz (HF)
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	681 mm
<b>Memory</b>	User memory: 640 bits
<b>Min.Tensile Strength</b>	1020 N
<b>Operating Temperature</b>	-25 °C to +70 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	50 pcs.
<b>Variant</b>	Not Serrated
<b>Weight/Unit</b>	0.0161 kg
<b>Width (W)</b>	7.9 mm

**HF** ✓

**RoHS** ✓