

Technical data sheet

Article number:
111-01601

T50I



| | |
|---|--|
| Product Group | Cable Ties inside serrated |
| Material | Polyamide 6.6, high impact modified, heat and UV-stabilised (PA66HIRHSUV) |
| Colour | Black (BK) |
| Application Tool | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max. | 80.0 mm |
| Bundle Ø min. | 1.5 mm |
| Flammability | UL 94 HB |
| Halogen-free | Yes |
| Length (L) | 305.0 mm |
| Min.Tensile Strength | 225 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | pack |
| Pack Cont. | 1000 pcs. |
| Releasable Closure (Yes/No) | No |
| Thickness (T) | 1.2 mm |
| Toothing (Serration) | Inside Serrated |
| UL-File Number | E64139 |
| UV-resistant acc. to ASTM D6779 (Yes/No) | Yes |
| Variant | Inside Serrated |
| Width (W) | 4.6 mm |

