

## Technical data sheet

Article number:  
111-01627

**T40R**



<b>Product Group</b>	Cable Ties for temperatures up to + 105°C (heat stabilised)
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>Colour</b>	Natural (NA)
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
<b>Bundle Ø max.</b>	40.0 mm
<b>Bundle Ø min.</b>	1.5 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	175 mm
<b>Min.Tensile Strength</b>	180 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	BV 03856/H0 BV, csa-C22.2 no. 62275
<b>Thickness (T)</b>	1.15 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64963
<b>UV-resistant acc. to ASTM D6779 (Yes/No)</b>	No
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.0009 kg
<b>Width (W)</b>	4.0 mm

