


## Technical data sheet

Article number:  
111-01638

**T50RFIDCLA**



<b>Product Group</b>	Cable ties with integrated RFID transponder
<b>Product Family</b>	T50RFID – Low frequency (LF), blank
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Colour</b>	Yellow (YE)
<b>Application Tool</b>	EVOcut, EVO7i
<b>Bundle Ø max.</b>	50 mm
<b>Bundle Ø min.</b>	1.5 mm
<b>Data Retention</b>	Up to 60 years
<b>Fixation Method</b>	None
<b>Flammability</b>	UL 94 V2
<b>Frequency</b>	125 kHz (LF)
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	200 mm
<b>Memory</b>	User memory: 32 bits
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +85 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Type of RFID chip</b>	Unique 64
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.00175 kg
<b>Width (W)</b>	4.6 mm

HF ✓

RoHS ✓