

## Technical data sheet

**Article number:**  
**111-02053**

**GL600**

<b>Product Group</b>	Cable Ties for bundling wires in solar power systems
<b>Product Family</b>	Galvalok-Series in PA11 black
<b>Material</b>	Polyamide 11, UV-resistant (PA11W)
<b>Colour</b>	Black (BK)
<b>Application Range</b>	Outdoor Use, High Temperature and Outdoor Use
<b>Application Tool</b>	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Diameter max (metric)</b>	175 mm
<b>Bundle Ø min.</b>	15 mm
<b>Flammability</b>	UL 94 HB
<b>Length (L)</b>	605 mm
<b>Min.Tensile Strength</b>	480 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	25 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	IEC 62275, IEC 62275:2018, UL 62275
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.00317 kg
<b>Width (W)</b>	9.6 mm

