

## Technical data sheet

**Article number:**  
**111-02118**

**LK5**

|                                     |  |
|-------------------------------------|--|
| <b>Product Group</b>                | Cable ties in-between size to T-Series   |
| <b>Product Family</b>               | LK-Series  |
| <b>Material</b>                     | Polyamide 6.6, heat stabilised (PA66HS)  |
| <b>Colour</b>                       | Black (BK)   |
| <b>Application Tool</b>             | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Bundle Diameter max (metric)</b> | 150 mm   |
| <b>Bundle Ø min.</b>                | 12.0 mm  |
| <b>Flammability</b>                 | UL 94 V2   |
| <b>Halogen-free</b>                 | Yes  |
| <b>Length (L)</b>                   | 535 mm   |
| <b>Min.Tensile Strength</b>         | 1115 N   |
| <b>Operating Temperature</b>        | -40 °C to +105 °C  |
| <b>Package Content packed in</b>    | bag  |
| <b>Pack Cont.</b>                   | 50 pcs.  |
| <b>Releasable Closure (Yes/No)</b>  | No   |
| <b>Thickness (T)</b>                | 1.8 mm   |
| <b>Toothing (Serration)</b>         | Inside Serrated  |
| <b>Variant</b>                      | Inside Serrated  |
| <b>Width (W)</b>                    | 13.2 mm  |

