


## Technical data sheet

Article number:  
111-02127

**T120S**



<b>Product Group</b>	Cable Ties for higher chemical resistance for temperatures up to +115°C in Polypropylene
<b>Product Family</b>	T-Series in PP
<b>Material</b>	Polypropylene (PP)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	55.0 mm
<b>Bundle Ø min.</b>	5.0 mm
<b>Flammability</b>	UL 94 HB
<b>Halogen-free</b>	Yes
<b>Height (H)</b>	7.7 mm
<b>Length (L)</b>	225 mm
<b>Min.Tensile Strength</b>	267 N
<b>Operating Temperature</b>	-40 °C to +115 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Thickness (T)</b>	1.6 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	7.6 mm

HF ✓

RoHS ✓