

## Technical data sheet

**Article number:**  
**111-02198**

**LK5**

<b>Product Group</b>	Cable ties in-between size to T-Series
<b>Product Family</b>	LK-Series
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Colour</b>	Natural (NA)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Diameter max (metric)</b>	150 mm
<b>Bundle Ø min.</b>	12.0 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	535 mm
<b>Min.Tensile Strength</b>	1115 N
<b>Operating Temperature</b>	-40 °C to +85 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	50 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Thickness (T)</b>	1.8 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	13.2 mm

