

Technical data sheet

Article number:
111-02359

T18I



Product Group	Cable Ties for temperatures up to + 105°C (heat stabilised)
Product Family	T-Series in PA66HS natural
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Natural (NA)
Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	35.0 mm
Bundle Ø min.	1.5 mm
Flammability	UL 94 V2
Halogen-free	Yes
Height (H)	3.5 mm
Length (L)	145.0 mm
Min.Tensile Strength	80 N
Operating Temperature	-40 °C to +105 °C, (+145 °C, 500 h)
Package Content packed in	pcs.
Pack Cont.	1000 pcs.
Releasable Closure (Yes/No)	No
Specifications	ANSI/UL 62275, csa-C22.2 no. 62275, IEC 62275:2006
Thickness (T)	1.2 mm
Toothing (Serration)	Inside Serrated
UL-File Number	E85319
UV-resistant acc. to ASTM D6779 (Yes/No)	No
Variant	Inside Serrated
Weight/Unit	0.0003 kg
Width (W)	2.5 mm

