


## Technical data sheet

Article number:  
111-02574

**T18I**



|                                                 |                                                               |
|-------------------------------------------------|---------------------------------------------------------------|
| <b>Product Group</b>                            | Cable Ties Polyamide 6.6 standard                             |
| <b>Material</b>                                 | Polyamide 6.6 (PA66)                                          |
| <b>Colour</b>                                   | Natural (NA)                                                  |
| <b>Application Tool</b>                         | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP |
| <b>Bundle Ø max.</b>                            | 35.0 mm                                                       |
| <b>Bundle Ø min.</b>                            | 1.5 mm                                                        |
| <b>Flammability</b>                             | UL 94 V2                                                      |
| <b>Halogen-free</b>                             | Yes                                                           |
| <b>Height (H)</b>                               | 3.5 mm                                                        |
| <b>Length (L)</b>                               | 140.0 mm                                                      |
| <b>Min.Tensile Strength</b>                     | 80 N                                                          |
| <b>Operating Temperature</b>                    | -40 °C to +85 °C                                              |
| <b>Package Content packed in</b>                | pack                                                          |
| <b>Pack Cont.</b>                               | 1000 pcs.                                                     |
| <b>Releasable Closure (Yes/No)</b>              | No                                                            |
| <b>Specifications</b>                           | UL 62275                                                      |
| <b>Thickness (T)</b>                            | 1.2 mm                                                        |
| <b>Toothing (Serration)</b>                     | Inside Serrated                                               |
| <b>UL-File Number</b>                           | E64139                                                        |
| <b>UV-resistant acc. to ASTM D6779 (Yes/No)</b> | No                                                            |
| <b>Variant</b>                                  | Inside Serrated                                               |
| <b>Width (W)</b>                                | 2.5 mm                                                        |

