

## Technical data sheet

Article number:  
111-02660

T25LL



|                                                 |                                                      |
|-------------------------------------------------|------------------------------------------------------|
| <b>Product Group</b>                            | Cable Ties for outdoor use (UV-resistant)            |
| <b>Product Family</b>                           | T-Series in PA66W black                              |
| <b>Material</b>                                 | Polyamide 6.6, UV-resistant (PA66W)                  |
| <b>Colour</b>                                   | Black (BK)                                           |
| <b>Application Tool</b>                         | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i |
| <b>Bundle Ø max.</b>                            | 95.0 mm                                              |
| <b>Bundle Ø min.</b>                            | 1.5 mm                                               |
| <b>Flammability</b>                             | UL 94 V2                                             |
| <b>Halogen-free</b>                             | Yes                                                  |
| <b>Length (L)</b>                               | 330 mm                                               |
| <b>Min.Tensile Strength</b>                     | 110 N                                                |
| <b>Operating Temperature</b>                    | -40 °C to +85 °C, (+105 °C, 500 h)                   |
| <b>Package Content packed in</b>                | pcs.                                                 |
| <b>Pack Cont.</b>                               | 100 pcs.                                             |
| <b>Releasable Closure (Yes/No)</b>              | No                                                   |
| <b>Specifications</b>                           | ANSI/UL 62275, csa-C22.2 no. 62275                   |
| <b>Thickness (T)</b>                            | 1.4 mm                                               |
| <b>Toothing (Serration)</b>                     | Inside Serrated                                      |
| <b>UL-File Number</b>                           | E85319                                               |
| <b>UV-resistant acc. to ASTM D6779 (Yes/No)</b> | Yes                                                  |
| <b>Variant</b>                                  | Inside Serrated                                      |
| <b>Weight/Unit</b>                              | 0.001277 kg                                          |
| <b>Width (W)</b>                                | 2.8 mm                                               |

