


## Materiale datablad

Varenummer  
111-03011

T30R



|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| <b>Produktgruppe</b>               | Kabelbindere polyamid 6.6. standard                                 |
| <b>Produktsérie</b>                | T serien i PA66 sort                                                |
| <b>Materiale</b>                   | Polyamid 6.6 (PA66)                                                 |
| <b>Farve</b>                       | Sort (BK)                                                           |
| <b>Anbefalet monteringsværktøj</b> | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP |
| <b>Antal pr.</b>                   | pose                                                                |
| <b>Bredde (W)</b>                  | 3,5 mm                                                              |
| <b>Bundtdiameter max.</b>          | 35,0 mm                                                             |
| <b>Bundtdiameter min.</b>          | 1,5 mm                                                              |
| <b>Driftstemperatur</b>            | -40 °C til +85 °C, (+105 °C, 500 h)                                 |
| <b>Flammehæmmende egenskab</b>     | Iht. UL94 V2                                                        |
| <b>Fortanding</b>                  | Indvendig fortanding                                                |
| <b>Genoplukkelig</b>               | Nej                                                                 |
| <b>Halogenfri</b>                  | Ja                                                                  |
| <b>Længde (L)</b>                  | 150 mm                                                              |
| <b>Min. trækstyrke</b>             | 135 N                                                               |
| <b>Pakkeindhold</b>                | 100 Stk.                                                            |
| <b>Tykkelse (T)</b>                | 1,1 mm                                                              |
| <b>Variant</b>                     | Indvendig fortanding                                                |

