

## **Technical data sheet**

**Article number:** 

111-04403 T30LR

[P]		
Cable Ties for temperatures up to + 105°C (heat stabilised)		
T-Series in PA66HS coloured		
Polyamide 6.6, heat stabilised (PA66HS)		
Brown (BN)		
	Cable Ties for temperatures up to + 105°C (heat stabilised) T-Series in PA66HS coloured Polyamide 6.6, heat stabilised (PA66HS)	

Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
Bundle Ø max.	65.0 mm
Bundle Ø min.	1.5 mm
Flammability	UL 94 V2
Halogen-free	Yes
Length (L)	260 mm
Min.Tensile Strength	180 N
Operating Temperature	-40 °C to +105 °C, (+145 °C, 500 h)
Package Content packed in	bag
Pack Cont.	100 pcs.
Releasable Closure (Yes/No)	No
Specifications	BV 03856/H0 BV
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/No)	No
Variant	Inside Serrated
Weight/Unit	0.00109 kg
Width (W)	3.3 mm



