


Materiale datablad

Varenummer
111-04889

T50R



Produktgruppe	Kabelbindere til udendørs anvendelse (UV resistant)
Produktserie	T serien i PA66W Sort
Materiale	Polyamid 6.6 UV-resistent (PA66W)
Farve	Sort (BK)
Anbefalet monteringsværktøj	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Antal pr.	pose
Bredde (W)	4,6 mm
Bundtdiameter max.	50,0 mm
Bundtdiameter min.	1,5 mm
Driftstemperatur	-40 °C til +85 °C, (+105 °C, 500 h)
Flammehæmmende egenskab	Iht. UL94 V2
Fortanding	Indvendig fortanding
Genoplukkelig	Nej
Halogenfri	Ja
Længde (L)	200 mm
Min. trækstyrke	225 N
Pakkeindhold	100 Stk.
Specifikation	IEC 62275:2006
Tykkelse (T)	1,2 mm
UV resistent ASTM D6779	Ja
Variant	Indvendig fortanding
Vægt	0,0013 kg

