

## **Technical data sheet**

**Article number:** 

111-04928 T50R

|  | IW |
|--|----|
|  |    |
|  |    |
|  |    |

| Product Group  | Cable Ties for higher chemical resistance for temperatures up to +115 °C in Polypropylene |
|----------------|---|
| Product Family | T-Series in PP  |
| Material       | Polypropylene (PP)  |
| Colour         | Black (BK)  |

| Application Tool                         | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
|--|--|
| Bundle Ø max.                            | 44.5 mm  |
| Bundle Ø min.                            | 12.7 mm  |
| Flammability                             | UL 94 HB   |
| Halogen-free                             | Yes  |
| Length (L)                               | 202.0 mm   |
| Min.Tensile Strength                     | 110 N  |
| Operating Temperature                    | -40 °C to +115 °C  |
| Package Content packed in                | pack   |
| Pack Cont.                               | 100 pcs.   |
| Releasable Closure (Yes/No)              | No   |
| Thickness (T)                            | 1.2 mm   |
| Toothing (Serration)                     | Inside Serrated  |
| UV-resistant acc. to ASTM D6779 (Yes/No) | No   |
| Variant                                  | Inside Serrated  |
| Weight/Unit                              | 0.001 kg   |
| Width (W)                                | 4.6 mm   |

