

Technical data sheet

Article number:
111-05018

T50R



| | |
|------------------------------------|--|
| Product Group | Cable ties made from post-industrial recycled polyamide 6.6 |
| Product Family | T-Series in PA66HIRHS(REC) black |
| Material | Polyamide 6.6 recycled, high impact modified, heat stabilised (PA66HIRHS(REC)) |
| Colour | Black (BK) |
| Application Tool | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| Bundle Ø max. | 50.0 mm |
| Bundle Ø min. | 1.5 mm |
| Halogen-free | Yes |
| Length (L) | 200 mm |
| Min.Tensile Strength | 225 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | bag |
| Pack Cont. | 100 pcs. |
| Releasable Closure (Yes/No) | No |
| Thickness (T) | 1.2 mm |
| Toothing (Serration) | Inside Serrated |
| Variant | Inside Serrated |
| Weight/Unit | 0.001545 kg |
| Width (W) | 4.6 mm |

