


Technical data sheet

Article number:
111-05421

T50L



Product Group	Cable Ties Polyamide 6.6 standard
Product Family	T-Series in PA66 natural
Material	Polyamide 6.6 (PA66)
Application Tool	ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP
Bundle Ø max.	110 mm
Bundle Ø min.	1.5 mm
Flammability	UL 94 V2
Halogen-free	Yes
Length (L)	390.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
Package Content packed in	bag
Pack Cont.	500 pcs.
Releasable Closure (Yes/No)	No
Specifications	ANSI/UL 1565, ANSI/UL 62275, ANSI/UL 746B, BV 03856/H0 BV, csa-C22.2 no. 18.5, csa-C22.2 no. 62275, IEC 62275:2006
Thickness (T)	1.4 mm
Toothing (Serration)	Inside Serrated
UL-File Number	E64963
Variant	Inside Serrated
Width (W)	4.6 mm

