


## Materiale datablad

Varenummer  
111-05860

T50S



|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Produktgruppe</b>               | Kabelbindere til udendørs brug (UV resistent)                                                                          |
| <b>Produktserie</b>                | T serien PA66W sort                                                                                                    |
| <b>Materiale</b>                   | Polyamid 6.6 UV-resistent (PA66W)                                                                                      |
| <b>Farve</b>                       | Sort (BK)                                                                                                              |
| <b>Anbefalet monteringsværktøj</b> | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Antal pr.</b>                   | styk                                                                                                                   |
| <b>Bredde (W)</b>                  | 4,6 mm                                                                                                                 |
| <b>Bundtdiameter max.</b>          | 35,0 mm                                                                                                                |
| <b>Bundtdiameter min.</b>          | 1,5 mm                                                                                                                 |
| <b>Driftstemperatur</b>            | -40 °C til +85 °C, (+105 °C, 500 h)                                                                                    |
| <b>Flammehæmmende egenskab</b>     | Iht. UL94 V2                                                                                                           |
| <b>Fortanding</b>                  | Indvendig fortanding                                                                                                   |
| <b>Genoplukkelig</b>               | Nej                                                                                                                    |
| <b>Halogenfri</b>                  | Ja                                                                                                                     |
| <b>Længde (L)</b>                  | 150 mm                                                                                                                 |
| <b>Min. trækstyrke</b>             | 225 N                                                                                                                  |
| <b>Pakkeindhold</b>                | 100 Stk.                                                                                                               |
| <b>Specifikation</b>               | IEC 62275:2006                                                                                                         |
| <b>Tykkelse (T)</b>                | 1,2 mm                                                                                                                 |
| <b>UV resistent ASTM D6779</b>     | Ja                                                                                                                     |
| <b>Variant</b>                     | Indvendig fortanding                                                                                                   |
| <b>Vægt</b>                        | 0,0012 kg                                                                                                              |

