


Materiale datablad

Varenummer
111-12050

T120R(E)



Produktgruppe	Kabelbindere beregnet for temperatur op til + 105°C (varme stabiliseret)
Produktserie	T serien i PA66HS sort
Materiale	Polyamid 6.6, varmestabiliseret (PA66HS)
Farve	Sort (BK)
Anbefalet monteringsværktøj	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Antal pr.	styk
Bredde (W)	7,6 mm
Bundtdiameter max.	100 mm
Bundtdiameter min.	3,0 mm
Driftstemperatur	-40 °C til +105 °C, (+145 °C, 500 h)
Flammehæmmende egenskab	Iht. UL94 V2
Fortanding	Indvendig fortanding
Genoplukkelig	Nej
Halogenfri	Ja
Længde (L)	387 mm
Min. trækstyrke	535 N
Pakkeindhold	100 Stk.
Specifikation	csa-C22.2 no. 62275, IEC 60092 series
Tykkelse (T)	1,8 mm
UL fil nummer	E64963
UV resistent ASTM D6779	Nej
Variant	Indvendig fortanding
Vægt	0,0052 kg

