Technical data sheet

Article number: 111-12066	T120R
L	
Product Group	Cable Ties for higher chemical resistance for temperatures up to +115 °C in Polypropylene
Product Family	T-Series in PP
Material	Polypropylene (PP)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	105.0 mm
Bundle Ø min.	5.0 mm
Flammability	UL 94 HB
Halogen-free	Yes
Height (H)	7.35 mm
Length (L)	387.0 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +115 °C
Package Content packed in	pack
Pack Cont.	500 pcs.
Releasable Closure (Yes/No)	No
Thickness (T)	1.8 mm
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/ No)	No
Variant	Inside Serrated
Weight/Unit	0.0044 kg
Width (W)	7.6 mm

HF RoHS

Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.