

Technical data sheet

Article number:
111-12203

T120I



Product Group	Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack
Product Family	T-Series in PA66HIR(S)
Material	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	80.0 mm
Bundle Ø min.	4.8 mm
Flammability	UL 94 HB
Halogen-free	Yes
Height (H)	7.7 mm
Length (L)	300 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +80 °C, (+105 °C, 500 h)
Package Content packed in	bag
Pack Cont.	100 pcs.
Releasable Closure (Yes/No)	No
Specifications	IEC 60092 series
Thickness (T)	1.6 mm
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/No)	No
Variant	Inside Serrated
Weight/Unit	0.003 kg
Width (W)	7.6 mm

