


Materiale datablad

Varenummer
111-12203

T120I



Produktgruppe	Kabelbindere med større modstandsdygtighed Polyamid 6.6 ScanBlack
Produktserie	T serien PA66 HIR(S)
Materiale	Polyamid 6.6 slagfast scan black (PA66HIR(S))
Farve	Sort (BK)
Anbefalet monteringsværktøj	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Antal pr.	pose
Bredde (W)	7,6 mm
Bundtdiameter max.	80,0 mm
Bundtdiameter min.	4,8 mm
Driftstemperatur	-40 °C til +80 °C, (+105 °C, 500 h)
Flammehæmmende egenskab	Iht. UL94 HB
Fortanding	Indvendig fortanding
Genoplukkelig	Nej
Halogenfri	Ja
Højde (H)	7,7 mm
Længde (L)	300 mm
Min. trækstyrke	535 N
Pakkeindhold	100 Stk.
Specifikation	IEC 60092 series
Tykkelse (T)	1,6 mm
UV resistent ASTM D6779	Nej
Variant	Indvendig fortanding
Vægt	0,003 kg

