

Technical data sheet

Article number:

Toothing (Serration)

Variant

Weight/Unit

Width (W)

111-12401 T120L

Product Group Cable Ties for temperatures up to + 195 °C (500 h) in Polyamide 4.6 Product Family T-Series in PA46 Material Polyamide 4.6 (PA46) Colour Black (BK) Application Tool ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9HT, EVO9i, EVO9iSP, EVO9HT Bundle Ø max. 225 mm Bundle Ø min. 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in Pack Cont. So pcs. Releasable Closure (Yes/No) No Thickness (T) 1.9 mm	L	
Product FamilyT-Series in PA46MaterialPolyamide 4.6 (PA46)ColourBlack (BK)Application ToolProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9HT, EVO9isP, EVO9iHTBundle Ø max.225 mmBundle Ø min.5.0 mmFlammabilityUL 94 V2Height (H)7.8 mmLength (L)760.0 mmMin.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No		IW
Product FamilyT-Series in PA46MaterialPolyamide 4.6 (PA46)ColourBlack (BK)Application ToolProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9HT, EVO9isP, EVO9iHTBundle Ø max.225 mmBundle Ø min.5.0 mmFlammabilityUL 94 V2Height (H)7.8 mmLength (L)760.0 mmMin.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No		
MaterialPolyamide 4.6 (PA46)ColourBlack (BK)Application ToolProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHTBundle Ø max.225 mmBundle Ø min.5.0 mmFlammabilityUL 94 V2Height (H)7.8 mmLength (L)760.0 mmMin.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Product Group	Cable Ties for temperatures up to + 195 °C (500 h) in Polyamide 4.6
Application Tool ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT Bundle Ø max. 225 mm Bundle Ø min. 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in Pack Cont. 50 pcs. Releasable Closure (Yes/No) No	Product Family	T-Series in PA46
Application Tool ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT Bundle Ø max. 225 mm 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Pack Gont. Beleasable Closure (Yes/No) No	Material	Polyamide 4.6 (PA46)
Bundle Ø max. 225 mm Bundle Ø min. 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in bag Pack Cont. 50 pcs. Releasable Closure (Yes/No) No	Colour	Black (BK)
Bundle Ø max. 225 mm Bundle Ø min. 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in bag Pack Cont. 50 pcs. Releasable Closure (Yes/No) No		
Bundle Ø min. 5.0 mm Flammability UL 94 V2 Height (H) 7.8 mm Length (L) 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in bag Pack Cont. 50 pcs. Releasable Closure (Yes/No) No	Application Tool	
FlammabilityUL 94 V2Height (H)7.8 mmLength (L)760.0 mmMin.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Bundle Ø max.	225 mm
Height (H) 7.8 mm 760.0 mm Min.Tensile Strength 535 N Operating Temperature -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) Package Content packed in bag Pack Cont. 50 pcs. Releasable Closure (Yes/No) No	Bundle Ø min.	5.0 mm
Length (L)760.0 mmMin.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Flammability	UL 94 V2
Min.Tensile Strength535 NOperating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Height (H)	7.8 mm
Operating Temperature-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Length (L)	760.0 mm
Package Content packed inbagPack Cont.50 pcs.Releasable Closure (Yes/No)No	Min.Tensile Strength	535 N
Pack Cont. 50 pcs. Releasable Closure (Yes/No) No	Operating Temperature	-40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h)
Releasable Closure (Yes/No) No	Package Content packed in	bag
	Pack Cont.	50 pcs.
Thickness (T) 1 9 mm	Releasable Closure (Yes/No)	No
	Thickness (T)	1.9 mm

LFH RoHS

Inside Serrated

Inside Serrated

0.0115 kg

7.6 mm