

Technical data sheet

Article number:
111-12402

T120L



| | |
|---|--|
| Product Group | Cable Ties for higher impact resistant Polyamide 6.6 ScanBlack |
| Product Family | T-Series in PA66HIR(S) |
| Material | Polyamide 6.6, high impact modified, scan black (PA66HIR(S)) |
| Colour | Black (BK) |
| Application Tool | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| Bundle Ø max. | 225 mm |
| Bundle Ø min. | 5.0 mm |
| Flammability | UL 94 HB |
| Halogen-free | Yes |
| Height (H) | 7.8 mm |
| Length (L) | 760.0 mm |
| Min.Tensile Strength | 535 N |
| Operating Temperature | -40 °C to +80 °C, (+105 °C, 500 h) |
| Package Content packed in | bag |
| Pack Cont. | 50 pcs. |
| Releasable Closure (Yes/No) | No |
| Specifications | IEC 60092 series |
| Thickness (T) | 1.9 mm |
| Toothing (Serration) | Inside Serrated |
| UV-resistant acc. to ASTM D6779 (Yes/No) | Yes |
| Variant | Inside Serrated |
| Weight/Unit | 0.0115 kg |
| Width (W) | 7.6 mm |

