Technical data sheet

Article number: 111-12440	T120L
L	
Product Group	Cable Ties for temperatures up to + 105°C (heat stabilised)
Product Family	T-Series in PA66HS black
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	225.0 mm
Bundle Ø min.	5.0 mm
Flammability	UL 94 V2
Halogen-free	Yes
Height (H)	7.8 mm
Length (L)	760.0 mm
Min.Tensile Strength	535 N
Operating Temperature	-40 °C to +105 °C, (+145 °C, 500 h)
Package Content packed in	pcs.
Pack Cont.	50 pcs.
Releasable Closure (Yes/No)	No
Specifications	IEC 60092 series
Thickness (T)	1.8 mm
Toothing (Serration)	Inside Serrated
UV-resistant acc. to ASTM D6779 (Yes/ No)	No
Variant	Inside Serrated
Weight/Unit	0.011611 kg
Width (W)	7.6 mm
	HF RoHS



Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.