

## Materiale datablad

Varenummer  
111-12440

T120L



|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Produktgruppe</b>               | Kabelbindere beregnet for temperatur op til + 105°C (varme stabiliseret)                                           |
| <b>Produktserie</b>                | T serien i PA66HS sort                                                                                             |
| <b>Materiale</b>                   | Polyamid 6.6, varmestabiliseret (PA66HS)                                                                           |
| <b>Farve</b>                       | Sort (BK)                                                                                                          |
| <b>Anbefalet monteringsværktøj</b> | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Antal pr.</b>                   | styk                                                                                                               |
| <b>Bredde (W)</b>                  | 7,6 mm                                                                                                             |
| <b>Bundtdiameter max.</b>          | 225,0 mm                                                                                                           |
| <b>Bundtdiameter min.</b>          | 5,0 mm                                                                                                             |
| <b>Driftstemperatur</b>            | -40 °C til +105 °C, (+145 °C, 500 h)                                                                               |
| <b>Flammehæmmende egenskab</b>     | Iht. UL94 V2                                                                                                       |
| <b>Fortanding</b>                  | Indvendig fortanding                                                                                               |
| <b>Genoplukkelig</b>               | Nej                                                                                                                |
| <b>Halogenfri</b>                  | Ja                                                                                                                 |
| <b>Højde (H)</b>                   | 7,8 mm                                                                                                             |
| <b>Længde (L)</b>                  | 760,0 mm                                                                                                           |
| <b>Min. trækstyrke</b>             | 535 N                                                                                                              |
| <b>Pakkeindhold</b>                | 50 Stk.                                                                                                            |
| <b>Specifikation</b>               | IEC 60092 series                                                                                                   |
| <b>Tykkelse (T)</b>                | 1,8 mm                                                                                                             |
| <b>UV resistent ASTM D6779</b>     | Nej                                                                                                                |
| <b>Variant</b>                     | Indvendig fortanding                                                                                               |
| <b>Vægt</b>                        | 0,011611 kg                                                                                                        |

