

## Technical data sheet

Article number:  
111-14819

**T150R**



|   |  |
|---|--|
| <b>Product Group</b>                            | Cable Ties Polyamide 6.6 standard  |
| <b>Product Family</b>                           | T-Series in PA66 natural   |
| <b>Material</b>                                 | Polyamide 6.6 (PA66)   |
| <b>Colour</b>                                   | Natural (NA)   |
| <b>Application Range</b>                        | Indoor Use   |
| <b>Application Tool</b>                         | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Bundle Ø max.</b>                            | 100.0 mm   |
| <b>Bundle Ø min.</b>                            | 5.0 mm   |
| <b>Flammability</b>                             | UL 94 V2   |
| <b>Halogen-free</b>                             | Yes  |
| <b>Length (L)</b>                               | 365 mm   |
| <b>Min.Tensile Strength</b>                     | 670 N  |
| <b>Operating Temperature</b>                    | -40 °C to +85 °C, (+105 °C, 500 h)   |
| <b>Package Content packed in</b>                | pcs.   |
| <b>Pack Cont.</b>                               | 100 pcs.   |
| <b>Releasable Closure (Yes/No)</b>              | No   |
| <b>Thickness (T)</b>                            | 1.6 mm   |
| <b>Toothing (Serration)</b>                     | Inside Serrated  |
| <b>UV-resistant acc. to ASTM D6779 (Yes/No)</b> | No   |
| <b>Variant</b>                                  | Inside Serrated  |
| <b>Weight/Unit</b>                              | 0.0056 kg  |
| <b>Width (W)</b>                                | 7.6 mm   |

