


Technical data sheet

Article number:
111-15305

T150XLL



Product Group	Cable Ties for outdoor use (UV-resistant)
Product Family	T-Series in PA66W black
Material	Polyamide 6.6, UV-resistant (PA66W)
Colour	Black (BK)
Application Range	Outdoor Use
Application Tool	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
Bundle Ø max.	405.0 mm
Bundle Ø min.	152.0 mm
Flammability	UL 94 V2
Halogen-free	Yes
Length (L)	1325.0 mm
Min.Tensile Strength	780 N
Operating Temperature	-40 °C to +85 °C
Package Content packed in	pack
Pack Cont.	25 pcs.
Releasable Closure (Yes/No)	No
Specifications	ANSI/UL 1565, ANSI/UL 62275, ANSI/UL 746B
Thickness (T)	2.1 mm
Toothing (Serration)	Inside Serrated
UL-File Number	E64139
UV-resistant acc. to ASTM D6779 (Yes/No)	Yes
Variant	Inside Serrated
Weight/Unit	0.0208 kg
Width (W)	8.9 mm

