

## Materiale datablad

Varenummer  
111-15502

T150XL



|                                    |                                                                                                      |
|------------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Produktgruppe</b>               | Kabelbindere til udendørs brug (UV resistent)                                                        |
| <b>Produktserie</b>                | T serien PA66W sort                                                                                  |
| <b>Materiale</b>                   | Polyamid 6.6 UV-resistent (PA66W)                                                                    |
| <b>Farve</b>                       | Sort (BK)                                                                                            |
| <b>Anbefalet monteringsværktøj</b> | ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| <b>Antal pr.</b>                   | pakke                                                                                                |
| <b>Bredde (W)</b>                  | 8,9 mm                                                                                               |
| <b>Bundtdiameter max.</b>          | 330,0 mm                                                                                             |
| <b>Bundtdiameter min.</b>          | 152,0 mm                                                                                             |
| <b>Driftstemperatur</b>            | -40 °C til +85 °C                                                                                    |
| <b>Flammehæmmende egenskab</b>     | Iht. UL94 V2                                                                                         |
| <b>Fortanding</b>                  | Indvendig fortanding                                                                                 |
| <b>Genoplukkelig</b>               | Nej                                                                                                  |
| <b>Halogenfri</b>                  | Ja                                                                                                   |
| <b>Længde (L)</b>                  | 1095,0 mm                                                                                            |
| <b>Min. trækstyrke</b>             | 780 N                                                                                                |
| <b>Pakkeindhold</b>                | 25 Stk.                                                                                              |
| <b>Specifikation</b>               | ANSI/UL 1565, ANSI/UL 62275, ANSI/UL 746B                                                            |
| <b>Tykkelse (T)</b>                | 2,1 mm                                                                                               |
| <b>UL fil nummer</b>               | E64139                                                                                               |
| <b>UV resistent ASTM D6779</b>     | Ja                                                                                                   |
| <b>Variant</b>                     | Indvendig fortanding                                                                                 |
| <b>Vægt</b>                        | 0,023664 kg                                                                                          |

