

## Technical data sheet

Article number:  
111-15609

**T150M**



<b>Product Group</b>	Cable Ties for temperatures up to + 105°C (heat stabilised)
<b>Product Family</b>	T-Series in PA66HS black
<b>Material</b>	Polyamide 6.6, heat stabilised (PA66HS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, MK9P, MK9P w/ Upper air, MK10-SB, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	150.0 mm
<b>Bundle Ø min.</b>	8.0 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	530.0 mm
<b>Min.Tensile Strength</b>	780 N
<b>Operating Temperature</b>	-40 °C to +125 °C
<b>Package Content packed in</b>	pack
<b>Pack Cont.</b>	25 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	UL 62275
<b>Thickness (T)</b>	2 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64139
<b>UV-resistant acc. to ASTM D6779 (Yes/No)</b>	No
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.0084 kg
<b>Width (W)</b>	8.9 mm

