


## Technical data sheet

Article number:  
111-24601

T250L



|   |   |
|---|---|
| <b>Product Group</b>                            | Cable Ties Polyamide 6.6 standard   |
| <b>Product Family</b>                           | T-Series in PA66 black  |
| <b>Material</b>                                 | Polyamide 6.6 (PA66)  |
| <b>Colour</b>                                   | Black (BK)  |
| <b>Application Tool</b>                         | ProCut 9 no battery, MK9P, MK9P w/ Upper air, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9ISP, EVO9iHT |
| <b>Bundle Ø max.</b>                            | 254.0 mm  |
| <b>Bundle Ø min.</b>                            | 12.0 mm   |
| <b>Flammability</b>                             | UL 94 V2  |
| <b>Halogen-free</b>                             | Yes   |
| <b>Height (H)</b>                               | 9.5 mm  |
| <b>Length (L)</b>                               | 880.0 mm  |
| <b>Min.Tensile Strength</b>                     | 1115 N  |
| <b>Operating Temperature</b>                    | -40 °C to +85 °C  |
| <b>Package Content packed in</b>                | pack  |
| <b>Pack Cont.</b>                               | 25 pcs.   |
| <b>Releasable Closure (Yes/No)</b>              | No  |
| <b>Specifications</b>                           | UL 62275  |
| <b>Thickness (T)</b>                            | 2.2 mm  |
| <b>Toothing (Serration)</b>                     | Inside Serrated   |
| <b>UL-File Number</b>                           | E64139  |
| <b>UV-resistant acc. to ASTM D6779 (Yes/No)</b> | No  |
| <b>Variant</b>                                  | Inside Serrated   |
| <b>Weight/Unit</b>                              | 0.0155 kg   |
| <b>Width (W)</b>                                | 12.4 mm   |

