

## Technical data sheet

**Article number:**  
**111-60160**

**LK2A**

<b>Product Group</b>	Cable ties in-between size to T-Series
<b>Product Family</b>	LK-Series
<b>Material</b>	Polyamide 6.6, UV-resistant (PA66W)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7ISP
<b>Bundle Ø max.</b>	73.0 mm
<b>Bundle Ø min.</b>	5.0 mm
<b>Flammability</b>	UL 94 V2
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	270 mm
<b>Min.Tensile Strength</b>	225 N
<b>Operating Temperature</b>	-40 °C to +85 °C
<b>Package Content packed in</b>	pcs.
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	IEC 60092 series
<b>Thickness (T)</b>	1.4 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.0011 kg
<b>Width (W)</b>	4.6 mm

