

Technical data sheet

Article number:
111-60559

LK5

| | |
|-----------------------------|--|
| Product Group | Cable ties in-between size to T-Series |
| Product Family | LK-Series |
| Material | Polyamide 6.6, heat stabilised (PA66HS) |
| Colour | Natural (NA) |
| Application Tool | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| Bundle Ø max. | 150 mm |
| Bundle Ø min. | 12.0 mm |
| Flammability | UL 94 V2 |
| Halogen-free | Yes |
| Length (L) | 535 mm |
| Min.Tensile Strength | 1115 N |
| Operating Temperature | -40 °C to +105 °C |
| Package Content packed in | pcs. |
| Pack Cont. | 50 pcs. |
| Releasable Closure (Yes/No) | No |
| Specifications | csa-C22.2 no. 62275, IEC 60092 series |
| Thickness (T) | 1.8 mm |
| Toothing (Serration) | Inside Serrated |
| UL-File Number | E64963 |
| Variant | Inside Serrated |
| Weight/Unit | 0.016 kg |
| Width (W) | 13.2 mm |

