


Technical data sheet

Article number:

Product Group

111-85350 T50SD6



1100000	Theee tixing hes with thownead, with bise
Product Family	for round holes
Material	Polyamide 6.6, heat stabilised (PA66HS)
Colour	Black (BK)
Application Tool	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO7, EVO7SP, EVO7iSP, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9HT
Bundle Ø max.	31.0 mm
Bundle Ø min.	1.5 mm
Fixation Method	arrowhead
Flammability	UL 94 V2
for Hole Ø (FH)	6.3 - 7.5 mm
Length (L)	160.0 mm
Min.Tensile Strength	225 N
Operating Temperature	-40 °C to +105 °C, (+145 °C, 500 h)
Package Content packed in	bag
Pack Cont.	500 pcs.
Panel Thickness	1.8 mm
Panel Thickness max.	0.6 – 1.8 mm
Panel Thickness min. (metric)	0.6 mm
ROHS compliant	Yes
Thickness (T)	1.5 mm
Variant	Inside Serrated
Width (W)	5.0 mm

1-Piece Fixing Ties with Arrowhead, with Disc

