Technical data sheet

Article number: 112-00065

Width (W)

LPT40I

Product GroupCable ties with low profile headProduct FamilyLow Head TieMaterialPolyamide 6.6, heat stabilised (PA66HS)ColourBlack (BK)Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.75.2 mmBundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmØin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack		
MaterialPolyamide 6.6, heat stabilised (PA66HS)ColourBlack (BK)Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.75.2 mmBundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmØin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Product Group	Cable ties with low profile head
ColourBlack (BK)Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.75.2 mmBundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Product Family	Low Head Tie
Application ToolMK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSPBundle Ø max.75.2 mmBundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Material	Polyamide 6.6, heat stabilised (PA66HS)
Bundle Ø max.75.2 mmBundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Colour	Black (BK)
Bundle Ø min.1.8 mmFlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Application Tool	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7iSP
FlammabilityUL 94 V2Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Bundle Ø max.	75.2 mm
Halogen-freeYesLength (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Bundle Ø min.	1.8 mm
Length (L)263.7 mmMin.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Flammability	UL 94 V2
Min.Tensile Strength180 NOperating Temperature-40 °C to +125 °CPackage Content packed inpack	Halogen-free	Yes
Operating Temperature-40 °C to +125 °CPackage Content packed inpack	Length (L)	263.7 mm
Package Content packed in pack	Min.Tensile Strength	180 N
	Operating Temperature	-40 °C to +125 °C
	Package Content packed in	pack
Pack Cont. 1000 pcs.	Pack Cont.	1000 pcs.
Variant Outside Serrated	Variant	Outside Serrated



3.6 mm

Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.