

Technical data sheet

Article number:
112-04019

T40R(U)



| | |
|---|---|
| Product Group | Cable Ties Polyamide 6.6 standard |
| Product Family | T-Series in PA66 natural |
| Material | Polyamide 6.6 (PA66) |
| Colour | Natural (NA) |
| Application Tool | MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP |
| Bundle Ø max. | 55.0 mm |
| Bundle Ø min. | 1.5 mm |
| Flammability | UL 94 V2 |
| Halogen-free | Yes |
| Length (L) | 210.82 mm |
| Min.Tensile Strength | 180 N |
| Operating Temperature | -40 °C to +85 °C |
| Package Content packed in | pack |
| Pack Cont. | 100 pcs. |
| Releasable Closure (Yes/No) | No |
| Specifications | UL 62275 |
| Thickness (T) | 1.15 mm |
| Toothing (Serration) | Inside Serrated |
| UL-File Number | E64139 |
| UV-resistant acc. to ASTM D6779 (Yes/No) | No |
| Variant | Inside Serrated |
| Weight/Unit | 0.0003 kg |
| Width (W) | 4.0 mm |

