HellermannTyton

Technical data sheet

L Product Group 1-piece fixing ties with mounting head for screws Product Family M-Series Material ProCut Family Application Tool ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7I, EVO7SP, EVO9, EVO9SP, EVO9i, EVO9iSP Bundle Ø max. 100.0 mm Bundle Ø min. 3.0 mm CE Certification Yes Fixation Method Screw Mount Hammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) 5.5 mm Height (L) 390.0 mm Min.Tensile Strength 225 N Mounting Screw Type #10 (M5) Screw Operating Temperature 40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated Vidth (W) 4.7 mm	Article number: 113-05403	T50ML
ØFH Product Group 1-piece fixing ties with mounting head for screws Product Family M-Series Material Polyamide 6.6 (PA66) Colour Natural (NA) Application Tool ProCut 9 no battery. MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9i, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP Bundle Ø max. 100.0 mm Bundle Ø min. 3.0 mm CE Certification Yes Fixation Method Screw Mount Flammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) S.84 mm Length (L) 390.0 mm Mounting Screw Type #10 (MS) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated	Ļ	
ØFH Product Group 1-piece fixing ties with mounting head for screws Product Family M-Series Material Polyamide 6.6 (PA66) Colour Natural (NA) Application Tool ProCut 9 no battery. MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9i, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP, EVO9iSP Bundle Ø max. 100.0 mm Bundle Ø min. 3.0 mm CE Certification Yes Fixation Method Screw Mount Flammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) S.84 mm Length (L) 390.0 mm Mounting Screw Type #10 (MS) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated		
Product Family M-Series Material Polyamide 6.6 (PA66) Colour Natural (NA) Application Tool ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7SP, EVO9i, EVO9iSP Bundle Ø max. 100.0 mm Bundle Ø min. 3.0 mm CE Certification Yes Fixation Method Screw Mount Flammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) 5.84 mm Length (L) 390.0 mm Mounting Screw Type #10 (M5) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated		
Product Family M-Series Material Polyamide 6.6 (PA66) Colour Natural (NA) Application Tool ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7SP, EVO9i, EVO9iSP Bundle Ø max. 100.0 mm Bundle Ø min. 3.0 mm CE Certification Yes Fixation Method Screw Mount Flammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) 5.84 mm Length (L) 390.0 mm Mounting Screw Type #10 (M5) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated		
MaterialPolyamide 6.6 (PA66)ColourNatural (NA)Application ToolProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7ISP, EVO9, EVO9SP, EVO9i, EVO9iSPBundle Ø max.100.0 mmBundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NMounting Screw Type#10 (MS) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Product Group	1-piece fixing ties with mounting head for screws
ColourNatural (NA)Application ToolProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7ISP, EVO9, EVO9SP, EVO9i, EVO9iSPBundle Ø max.100.0 mmBundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMounting Screw Type#10 (MS) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Product Family	M-Series
Application ToolProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7SP, EVO9, EVO9SP, EVO9i, EVO9SPBundle Ø max.100.0 mmBundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Material	Polyamide 6.6 (PA66)
Application foolEVO7iSP, EVO9, EVO9i, EVO9iSPBundle Ø max.100.0 mmBundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Colour	Natural (NA)
Application foolEVO7iSP, EVO9, EVO9i, EVO9iSPBundle Ø max.100.0 mmBundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated		
Bundle Ø min.3.0 mmCE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL -File NumberE64139VariantInside Serrated	Application Tool	
CE CertificationYesFixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMinTensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Bundle Ø max.	100.0 mm
Fixation MethodScrew MountFlammabilityUL 94 V2for Hole Ø (FH)5.5 mmHeight (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Bundle Ø min.	3.0 mm
Flammability UL 94 V2 for Hole Ø (FH) 5.5 mm Height (H) 5.84 mm Length (L) 390.0 mm Min.Tensile Strength 225 N Mounting Screw Type #10 (M5) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated	CE Certification	Yes
for Hole Ø (FH) 5.5 mm Height (H) 5.84 mm Length (L) 390.0 mm Min.Tensile Strength 225 N Mounting Screw Type #10 (M5) Screw Operating Temperature -40 °C to +85 °C Package Content packed in pack Pack Cont. 1000 pcs. ROHS compliant Yes Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated	Fixation Method	Screw Mount
Height (H)5.84 mmLength (L)390.0 mmMin.Tensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Flammability	UL 94 V2
Length (L)390.0 mmMin.Tensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	for Hole Ø (FH)	5.5 mm
Min.Tensile Strength225 NMounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Height (H)	5.84 mm
Mounting Screw Type#10 (M5) ScrewOperating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Length (L)	390.0 mm
Operating Temperature-40 °C to +85 °CPackage Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Min.Tensile Strength	225 N
Package Content packed inpackPack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Mounting Screw Type	#10 (M5) Screw
Pack Cont.1000 pcs.ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Operating Temperature	-40 °C to +85 °C
ROHS compliantYesSpecificationsUL 62275UL-File NumberE64139VariantInside Serrated	Package Content packed in	pack
Specifications UL 62275 UL-File Number E64139 Variant Inside Serrated	Pack Cont.	1000 pcs.
UL-File Number E64139 Variant Inside Serrated	ROHS compliant	Yes
Variant Inside Serrated	Specifications	UL 62275
	UL-File Number	E64139
Width (W) 4.7 mm	Variant	Inside Serrated
	Width (W)	4.7 mm

