

## Technical data sheet

Article number:  
114-00879

T18S



<b>Product Group</b>	Cable Ties for temperatures up to + 195 °C (500 h) in Polyamide 4.6
<b>Product Family</b>	T-Series in PA46
<b>Material</b>	Polyamide 4.6 (PA46)
<b>Colour</b>	Natural (NA)
<b>Application Range</b>	High Temperature and Outdoor Use
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP
<b>Bundle Ø max.</b>	16.0 mm
<b>Bundle Ø min.</b>	1.0 mm
<b>Flammability</b>	UL 94 V2
<b>Height (H)</b>	3.2 mm
<b>Length (L)</b>	80 mm
<b>Min.Tensile Strength</b>	80 N
<b>Operating Temperature</b>	-40 °C to +130 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	1000 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	ANSI/UL 1565, ANSI/UL 62275
<b>Thickness (T)</b>	1.0 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>UL-File Number</b>	E64962
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.000213 kg
<b>Width (W)</b>	2.2 mm

