

## Technical data sheet

Article number:  
115-00111

**RELK2R**

|                                     |                                               |
|-------------------------------------|-----------------------------------------------|
| <b>Product Group</b>                | Cable ties inside serrated                    |
| <b>Product Family</b>               | RELK-Series up to 200 N loop tensile strength |
| <b>Material</b>                     | Polyamide 6.6 (PA66)                          |
| <b>Colour</b>                       | Natural (NA)                                  |
|                                     |                                               |
| <b>Application Range</b>            | Indoor Use                                    |
| <b>Bundle Diameter max (metric)</b> | 50.0 mm                                       |
| <b>Bundle Ø min.</b>                | 5.0 mm                                        |
| <b>Flammability</b>                 | UL 94 V2                                      |
| <b>Length (L)</b>                   | 200 mm                                        |
| <b>Min.Tensile Strength</b>         | 225 N                                         |
| <b>Operating Temperature</b>        | -40 °C to +85 °C                              |
| <b>Package Content packed in</b>    | bag                                           |
| <b>Pack Cont.</b>                   | 100 pcs.                                      |
| <b>Releasable Closure (Yes/No)</b>  | Yes                                           |
| <b>Variant</b>                      | Inside Serrated                               |
| <b>Width (W)</b>                    | 4.6 mm                                        |

**RoHS** 