

## Technische datasheet

Artikel Nummer  
116-05416

T80L



|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Productgroep</b>                 | Bundelbanden diverse kleuren                                                                                           |
| <b>Productfamilie</b>               | T-serie in PA66 diverse kleuren                                                                                        |
| <b>Materiaal</b>                    | Polyamide 6.6 (PA66)                                                                                                   |
| <b>Kleur</b>                        | blauw (BU)                                                                                                             |
| <b>Brandbaarheid</b>                | UL94 V2                                                                                                                |
| <b>Breedte (W)</b>                  | 4,7 mm                                                                                                                 |
| <b>Bundel diameter Ø max.</b>       | 110 mm                                                                                                                 |
| <b>Bundel diameter Ø min.</b>       | 1,5 mm                                                                                                                 |
| <b>Dikte (T)</b>                    | 1,3 mm                                                                                                                 |
| <b>Gebruikstemperatuur - °C</b>     | -40 °C tot +85 °C, (+105 °C, 500 h)                                                                                    |
| <b>Gereedschappen</b>               | ProCut 9 no battery, MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7, EVO7SP, EVO7i, EVO7iSP, EVO9, EVO9SP, EVO9i, EVO9iSP |
| <b>Halogeenvrij</b>                 | ja                                                                                                                     |
| <b>Hersluitbare sluitkop ja/nee</b> | nee                                                                                                                    |
| <b>Hoeveelheid per</b>              | st.                                                                                                                    |
| <b>Inhoud</b>                       | 100 st.                                                                                                                |
| <b>Lengte (L)</b>                   | 390 mm                                                                                                                 |
| <b>Min. spankracht</b>              | 355 N                                                                                                                  |
| <b>Nettogewicht</b>                 | 0,0026 kg                                                                                                              |
| <b>Uitvoering</b>                   | binnenvertand                                                                                                          |
| <b>UV bestendig ASTM D6779</b>      | nee                                                                                                                    |
| <b>Vertanding</b>                   | binnenvertand                                                                                                          |

