


## Technical data sheet

Article number:  
116-15014

T150R(H)



|                                          |                                                                                                                    |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Product Group                            | Cable Ties Polyamide 6.6 standard                                                                                  |
| Product Family                           | T-Series in PA66 coloured                                                                                          |
| Material                                 | Polyamide 6.6 (PA66)                                                                                               |
| Colour                                   | Yellow (YE)                                                                                                        |
| Application Tool                         | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| Bundle Ø max.                            | 100 mm                                                                                                             |
| Bundle Ø min.                            | 5.0 mm                                                                                                             |
| Flammability                             | UL 94 V2                                                                                                           |
| Halogen-free                             | Yes                                                                                                                |
| Length (L)                               | 365 mm                                                                                                             |
| Min.Tensile Strength                     | 670 N                                                                                                              |
| Operating Temperature                    | -40 °C to +85 °C, (+105 °C, 500 h)                                                                                 |
| Package Content packed in                | pcs.                                                                                                               |
| Pack Cont.                               | 100 pcs.                                                                                                           |
| Releasable Closure (Yes/No)              | No                                                                                                                 |
| Thickness (T)                            | 1.6 mm                                                                                                             |
| Toothing (Serration)                     | Inside Serrated                                                                                                    |
| UV-resistant acc. to ASTM D6779 (Yes/No) | No                                                                                                                 |
| Variant                                  | Inside Serrated                                                                                                    |
| Weight/Unit                              | 0.0046 kg                                                                                                          |
| Width (W)                                | 7.6 mm                                                                                                             |

